



mondial



# ACQUA PRO

Vetrine verticali positive  
Upright display coolers



TEMPERATURE RANGE

+2° +8 C

IDEAL FOR




**CARATTERISTICHE TECNICHE - Technical features**

	ACQUA PRO B	ACQUA PRO W
Temperatura - Temperature	+2°C +8°C	+2°C +8°C
Gas refrigerante - Refrigerant gas	R600a	R600a
Classe climatica - Climate Class	4 (30°C-55%UR) CC2	4 (30°C-55%UR) CC2
Dimensioni (L x p x h) - Sizes (w x d x h)	600 x 649 x 1801 mm	600 x 649 x 1801 mm
Peso netto - Net weight	79 kg	79 kg
Peso lordo - Gross weight	93 kg	93 kg
Volume Netto - Net volume	274 l	274 l
Volume Lordo - Gross volume	360 l	360 l
Potenza - Power	230 W	230 W
Consumo - Consumption	2,1 kWh/24h	2,1 kWh/24h
Dimensioni imballo (L x p x h) - Packaging sizes (w x d x h)	650 x 685 x 2005 mm	650 x 685 x 2005 mm
Dati per il trasporto - Transport data (20 ft - 40 ft - 40 hc - 13,60 mt)	27/54/54/60	27/54/54/60
Ripiani - Shelves	5 rimovibili / 5 removable	5 rimovibili / 5 removable
Classe energetica - Energy efficiency class		

✓ **2x Luce interna verticale a LED**  
2x Vertical internal LED light

✓ **Nuova porta totalmente vetrata**  
New fully glazed door

✓ **Rispetto ambientale: Gas R600a**  
Environmentally friendly: R600a Gas


**APPROFONDIMENTO - More details**

**Evaporatore ventilato a roll bond**  
Fan assisted roll bond evaporator

**Mobile in lamiera d'acciaio nera trattata anti corrosione (mod. B)**  
Black anti corrosion treated steel sheet cabinet (mod. B)

**Mobile in lamiera d'acciaio bianca trattata anti corrosione (mod. W)**  
White anti corrosion treated steel sheet cabinet (mod. W)

**Luci a led con interruttore (luce fredda)**  
LED lights with switch (cool light)

**Serratura**  
Lock

**2 piedini regolabili**  
2 adjustable feet



ACQUA PRO W


**ACCESSORI - Accessories**

Cod.	Optional
TDM202556	Griglia standard - Standard shelf
TDM202555	Griglia standard - Standard shelf

Modelli - Models

ACQUA W PRO

ACQUA B PRO