



# KIC P

Armadi refrigeranti e congelatori  
Upright refrigerators and freezers



TEMPERATURE RANGE

-2° +10° C

IDEAL FOR




**CARATTERISTICHE TECNICHE - Technical features**

	KIC PR 40 LIGHT TOUCH	KIC PRX 40 LIGHT TOUCH	KIC PR 60 LIGHT TOUCH	KIC PRX 60 LIGHT TOUCH	KIC PV 40 M LIGHT TOUCH	KIC PVX 40 M LIGHT TOUCH	KIC PV 60 M LIGHT TOUCH	KIC PVX 60 M LIGHT TOUCH
Marchio - Brand	Mondial		Mondial		Mondial		Mondial	
Temperatura - Temperature	+2°C +10°C		+2°C +10°C		-2°C +10°C		-2°C +10°C	
Gas refrigerante - Refrigerant gas	R600a		R134a/R600a		R134a/R600a		R600a	
Classe climatica - Climate Class	4 (30°C-55%UR)		4 (30°C-55%UR)		4 (30°C-55%UR)		4 (30°C-55%UR)	
Dimensioni (L x p x h) Sizes (w x d x h)	600 x 620 x 1872 mm		775 x 740 x 1872 mm		600 x 620 x 1872 mm		775 x 740 x 1872 mm	
Peso netto - Net weight	73,70		92,00		84,50		96,00	
Peso lordo - Gross weight	76,00		100,00		86,00		103,00	
Volume Netto - Net volume	275 l		465,1 l		253 l		458 l	
Volume Lordo - Gross volume	380 l		640 l		380 l		640 l	
Potenza - Power	120 W		310 W		160 W		145 W	
Consumo - Consumption	1,99 kWh/24h		3,2 kWh/24h		2,63 kWh/24h		1,63 kWh/24h	
Dimensioni imballo (L x p x h) Packaging sizes (w x d x h)	655 x 690 x 1930 mm		830 x 810 x 1965 mm		655 x 690 x 1930 mm		830 x 810 x 1965 mm	
Dati per il trasporto - Transport data (20 ft - 40 ft - 40 hc - 13,60 mt)	27/54/54/60		14/28/28/48		27/54/54/60		14/28/28/48	
Ripiani - Shelves	4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf	


**HIGHLIGHTS - Best features**
**Mobile in lamiera d'acciaio bianca trattata anti-corrosione mod. PR-PV**

White anticorrosion treated steel sheet cabinet mod. PR-PV

**Mobile in lamiera d'acciaio inox AISI 430 mod. PRX-PVX**

AISI 430 stainless steel sheet cabinet mod. PRX-PVX

**Vasca termoformata in plastica a norme alimentari**

Food safe thermoformed plastic tank

**Porta cieca con guarnizione magnetica**

Solid door with magnetic gasket

**Serratura**

Lock

**Evaporatore ventilato a roll bond mod. PR**

Fan assisted roll bond evaporator mod. PR

**Evaporatore ventilato a pacco alettato mod. PV**

Ventilated pack evaporator mod. PV

**Sistema condensante statico a fili (con agitatore)**

Wire tube static condensing system (fan assisted)

**Termostato-termometro elettronico con sbrinamento automatico**

Electronic thermostat-thermometer with automatic defrosting

**2 piedini regolabili**

2 adjustable feet

KIC PR 60


**ACCESSORI - Accessories**

Cod.	Optional	Modelli - Models
8998235F	Kit porta reversibile - Reversible door kit	TUTTI - ALL
8998389F	Pedale apri porta - Pedal for door opening	KIC 40
5601158	Pedale apri porta - Pedal for door opening	KIC 60
8998099F	Kit 4 ruote pivotanti (2 con freno) - 4 Pivoting wheel kit (2 with brake)	KIC 40
8998107F	Kit 4 ruote pivotanti (2 con freno) - 4 Pivoting wheel kit (2 with brake)	KIC 60
8998100F	Kit 4 piedi di rialzo - 4 Mounting foot kit	KIC 40
8998108F	Kit 4 piedi di rialzo - 4 Mounting foot kit	KIC 60
0621092	Griglia standard - Standard shelf (515 x 400mm)	KIC P 40 ALL
0621117	Griglia GN 2/1 - GN 2/1 Shelf (650 x 530mm)	KIC P 60 ALL
0621097	Griglia fondo vasca - Bottom shelf (505 x 250mm)	KIC P 40 ALL
0621109	Griglia fondo vasca - Bottom shelf (655 x 360mm)	KIC P 60 ALL
8998118F	Dispositivo elettrico d'evaporazione acque di condensa - Electrical evap. water system	TUTTI - ALL