



mondial



# KIC P

Armadi refrigerati  
Upright refrigerators



TEMPERATURE RANGE

-2° +10° C

IDEAL FOR




**CARATTERISTICHE TECNICHE - Technical features**

	KIC PR 40 LIGHT TOUCH	KIC PRX 40 LIGHT TOUCH	KIC PR 60 LIGHT TOUCH	KIC PRX 60 LIGHT TOUCH	KIC PV 40 M LIGHT TOUCH	KIC PVX 40 M LIGHT TOUCH	KIC PV 60 M LIGHT TOUCH	KIC PVX 60 M LIGHT TOUCH
Temperatura - <i>Temperature</i>	+2°C +10°C		+2°C +10°C		-2°C +10°C		-2°C +10°C	
Gas refrigerante - <i>Refrigerant gas</i>	R600a		R600a		R600a		R600a	
Classe climatica - <i>Climate Class</i>	4 (30°C-55%UR)		4 (30°C-55%UR)		4 (30°C-55%UR)		4 (30°C-55%UR)	
Dimensioni (L x p x h) <i>Sizes (w x d x h)</i>	600 x 620 x 1872 mm		775 x 740 x 1872 mm		600 x 620 x 1872 mm		775 x 740 x 1872 mm	
Peso netto - <i>Net weight</i>	73 kg		92 kg		84 kg		96 kg	
Peso lordo - <i>Gross weight</i>	76 kg		100 kg		86 kg		103 kg	
Volume Netto - <i>Net volume</i>	275 l		465.1 l		253 l		458 l	
Volume Lordo - <i>Gross volume</i>	380 l		640 l		380 l		640 l	
Potenza - <i>Power</i>	120 W		120 W		160 W		145 W	
Consumo - <i>Consumption</i>	1,99 kWh/24h		2,24 kWh/24h		1,63 kWh/24h		1,69 kWh/24h	
Dimensioni imballo (L x p x h) <i>Packaging sizes (w x d x h)</i>	655 x 690 x 1930 mm		830 x 810 x 1965 mm		655 x 690 x 1930 mm		830 x 810 x 1965 mm	
Dati per il trasporto - <i>Transport data</i> (20 ft - 40 ft - 40 hc - 13,60 mt)	27/54/54/60		14/28/28/48		27/54/54/60		14/28/28/48	
Ripiani - <i>Shelves</i>	4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf		4 rimovibili / removable + 1 fondo vasca / bottom shelf	
Classe energetica <i>Energy efficiency class</i>								

✓ **Più di 300.000 unità vendute nel mondo**  
Over 300.000 units sold in the world

✓ **Struttura robusta anti deterioramento**  
Anti deterioration strong structure

✓ **Rispetto ambientale: Gas R600a**  
Environmentally friendly: R600a Gas



KIC PR/PV

**APPROFONDIMENTO - More details**
**Evaporatore ventilato a roll bond (mod. PR)**

Fan assisted roll bond evaporator (mod. PR)

**Evaporatore ventilato a pacco alettato (mod. PV)**

Ventilated pack evaporator (mod. PV)

**Mobile in lamiera d'acciaio bianca trattata anti corrosione (mod. PR-PV)**

White anticorrosion treated steel sheet cabinet (mod. PR-PV)

**Mobile in lamiera d'acciaio inox AISI 430 (mod. PRX-PVX)**

AISI 430 stainless steel sheet cabinet (mod. PRX-PVX)

**Vasca termoformata in plastica a norme alimentari**

Food safe thermoformed plastic tank

**Serratura**

Lock

**2 piedini regolabili**

2 adjustable feet

**ACCESSORI - Accessories**

Cod.	Optional	Modelli - <i>Models</i>
8998235F	Kit porta reversibile - <i>Reversible door kit</i>	TUTTI - ALL
8998389F	Pedale apri porta - <i>Pedal for door opening</i>	KIC 40
5601158	Pedale apri porta - <i>Pedal for door opening</i>	KIC 60
8998099F	Kit 4 ruote pivotanti (2 con freno) - <i>4 Pivoting wheel kit (2 with brake)</i>	KIC 40
8998107F	Kit 4 ruote pivotanti (2 con freno) - <i>4 Pivoting wheel kit (2 with brake)</i>	KIC 60
8998100F	Kit 4 piedi di rialzo - <i>4 Mounting foot kit</i>	KIC 40
8998108F	Kit 4 piedi di rialzo - <i>4 Mounting foot kit</i>	KIC 60
0621092	Griglia standard - <i>Standard shelf (515 x 400 mm)</i>	KIC P 40 ALL
0621117	Griglia GN 2/1 - <i>GN 2/1 Shelf (650 x 530 mm)</i>	KIC P 60 ALL
8998118F	Dispositivo elettrico d'evaporazione acque di condensa - <i>Electrical evap. water system</i>	TUTTI - ALL