



MAEL

Congelatori orizzontali coperchio cieco
Hinged lid chest freezers



TEMPERATURE RANGE

-18° -25° C

IDEAL FOR




CARATTERISTICHE TECNICHE - Technical features

	MAEL 220	MAEL 300	MAEL 400	MAEL 500
Marchio - Brand	Easy by Mondial Framec	Easy by Mondial Framec	Easy by Mondial Framec	Easy by Mondial Framec
Temperatura - Temperature	-18°C -25°C	-18°C -25°C	-18°C -25°C	-18°C -25°C
Gas refrigerante - Refrigerant gas	R600a	R600a	R600a	R600a
Classe climatica - Climate Class	4+ (35°C-70%RH) L1	4+ (35°C-70%RH) L1	4+ (35°C-70%RH) L1	4+ (35°C-70%RH) L1
Dimensioni (L x p x h) - Sizes (w x d x h)	891 x 695 x 860 mm	1096 x 695 x 860 mm	1326 x 695 x 860 mm	1516 x 695 x 860 mm
Peso netto - Net weight	37,00	44,00	48,00	53,00
Peso lordo - Gross weight	39,00	47,00	51,00	57,00
Volume Netto - Net volume	209 l	278 l	349 l	411 l
Volume Lordo - Gross volume	211 l	281 l	352 l	414 l
Potenza - Power	87 W	130 W	160 W	210 W
Consumo - Consumption	0,84 kWh/24h	1,25 kWh/24h	1,54 kWh/24h	2,02 kWh/24h
Dimensioni imballo (L x p x h) - Packaging sizes (w x d x h)	950 x 710 x 880 mm	1160 x 710 x 880 mm	1390 x 710 x 880 mm	1580 x 710 x 880 mm
Dati per il trasporto - Transport data (20 ft - 40 ft - 40 hc - 13,60 mt)	42/72/112/94	40/66/96/76	28/50/75/56	25/46/69/54


HIGHLIGHTS - Best features
Mobile in lamiera d'acciaio preverniciata bianca trattata anti-corrosione

White prepainted corrosion proof steel cabinet body

Vasca in alluminio gofrato

Embossed aluminium sheet tank

Evaporatore statico avvolto sulla vasca

Foamed in evaporator pipe wrapped around the inner liner

Coperchio: superficie interna in plastica, esterna in lamiera plastificata bianca trattata anti-corrosione

Lid: inner side made of plastic, outer side made of white plasticized anti-corrosion treated sheet

Isolamento di 65 mm in poliuretano iniettato SENZA HCFC/CFC

65 mm insulation in injected polyurethane WITHOUT HCFC/CFC

Sistema condensante statico a fili

Wire tube static condensing system

Termostato meccanico con sbrinamento manuale

Mechanical thermostat with manual defrosting

Termometro meccanico

Mechanical thermometer

Luce interna

Internal light

Serratura

Lock

Commutatore di congelazione rapida, spie di allarme e di funzionamento

Fast freezing commutator, alarm and operation warning lights

4 rullini unidirezionali

4 one-way rollers

Possibilità di personalizzazione sui 3 lati

Customizable body (only 3 sides)


Cestello: 1 in dotazione

Basket: 1 standard


ACCESSORI - Accessories

Cod.	Optional	Modelli - Models
2601134	Cestello - Basket (500 x 250 x 215 mm)	TUTTI - ALL