



SIMPLEX

Vetrina per uso medicale

Glass door upright display cooler for medical use



TEMPERATURE RANGE

+3° +15° C

IDEAL FOR





CARATTERISTICHE TECNICHE - Technical features

	SIMPLEX
Marchio - Brand	Mondial Framec
Temperatura - Temperature	+3°C +15°C
Gas refrigerante - Refrigerant gas	R600a
Classe climatica - Climate Class	4 (30°C-55%UR)
Dimensioni (L x p x h) - Sizes (w x d x h)	600 x 654 x 840 mm
Peso netto - Net weight	50,00
Peso lordo - Gross weight	59,00
Volume Netto - Net volume	130 l
Volume Lordo - Gross volume	156 l
Potenza - Power	100 W
Consumo - Consumption	3 kWh/24h
Dimensioni imballo (L x p x h) - Packaging sizes (w x d x h)	650 x 705 x 1000 mm
Dati per il trasporto - Transport data (20 ft - 40 ft - 40 hc - 13,60 mt)	54/108/108/120
Ripiani - Shelves	4 rimovibili / removable



HIGHLIGHTS - Best features

Isolamento in poliuretano ecologico privo di espandenti ad alto effetto serra (HFC) o lesivi lo strato di ozono (HCFC)

Ecologic polyurethane insulation, without greenhouse effect (HFC) and ozone depleting (HCFC) foaming agent gases

Struttura esterna in lamiera d'acciaio plastificata di colore bianco

Pre-treated anticorrosion, metal sheet, white external structure

Rivestimento interno in lamiera d'acciaio verniciata di colore bianco, antibatterico

Pre-treated anticorrosion, antibacterial, metal sheet, white internal structure

Porta reversibile con telaio in alluminio verniciato a polvere bianco, profilo di taglio termico plastico con guarnizione asportabile, vetro camera isolante e trattamento di bassa emissività, alto isolante e antiappannante

Powder coating aluminium frame reversible white door, equipped with thermal break ABS plastic profile with changeable gasket and double pane with low-emissivity treatment, for high insulation and anti-mist effect

Maniglia esterna in ferro verniciata

External metal painted handle

4 ripiani griglia rimovibili correati di profilo porta-prezzo in plastica più 1 cestello di fondo vasca

4 internal, plastic coated, removable shelves, equipped with white plastic label-holder, plus 1 bottom tank basket

4 piedini regolabili

4 adjustable feet

Serratura

Lock

Termostato elettronico digitale, di facile utilizzo, per una precisa e agevole regolazione della temperatura e immediata visualizzazione degli allarmi. Dotato di schermo piatto, a LED verdi, altezza 16 mm e icone, consente la visualizzazione completa dello stato dell'apparecchio senza ingresso in programmazione, mediante la sola pressione di un tasto. Fornito con orologio interno per gestione eventi (giorno, mese, anno, giorno della settimana, ora e minuti) 6 mesi di backup.

Digital electronic thermostat, simple usage, for a precise and easy temperature regulation and an effective alarm visualization. Provided with flat display, 16 mm height green LEDs and status icons, it allows a complete visualization of the appliance status without entering in parameters list, by only pushing front keys. Equipped with internal clock for real time data (day, month, year, hour and minute), 6 months back-up.



ACCESSORI - Accessories

Cod.	Optional	Modelli - Models
8998425F	Kit sovrapposizione - Overlapping kit	SIMPLEX