



mondial



Sous-Chef

Tavoli refrigerati e congelatori
Refrigerated and freezers tables



GAS
R290



TEMPERATURE RANGE

-22° +8° C

IDEAL FOR




CARATTERISTICHE TECNICHE - Technical features

| | SOUS-CHEF 2 PX | SOUS-CHEF 2 NX | SOUS-CHEF 3 PX | SOUS-CHEF 3 NX | SOUS-CHEF 4 PX | SOUS-CHEF 4 NX |
|---|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Temperatura - <i>Temperature</i> | -2°C +8°C | -18°C -22°C | -2°C +8°C | -18°C -22°C | -2°C +8°C | -18°C -22°C |
| Gas refrigerante - <i>Refrigerant gas</i> | R290 | R290 | R290 | R290 | R290 | R290 |
| Classe climatica - <i>Climate Class</i> | 4 (30°C-55%UR) | 4 (30°C-55%UR) | 4 (30°C-55%UR) | 4 (30°C-55%UR) | 4 (30°C-55%UR) | 4 (30°C-55%UR) |
| Dimensioni (l x p x h) <i>Sizes (w x d x h)</i> | 1350 x 700 x 950 mm | | 1800 x 700 x 950 mm | | 2250 x 700 x 950 mm | |
| Peso netto - <i>Net weight</i> | 102 | 102 | 126 | 126 | 153 | 153 |
| Peso lordo - <i>Gross weight</i> | 127 | 142 | 158 | 180 | 196 | 210 |
| Volume Lordo - <i>Gross volume</i> | 260 l | 260 l | 400 l | 400 l | 570 l | 570 l |
| Potenza - <i>Power</i> | 350 W | 700 W | 350 W | 820 W | 330 W | 920 W |
| Consumo - <i>Consumption</i> | 2,5 kWh/24h | 6,1 kWh/24h | 2,9 kWh/24h | 7,3 kWh/24h | 3,8 kWh/24h | 7,7 kWh/24h |
| Dimensioni imballo (l x p x h) <i>Packaging sizes (w x d x h)</i> | 1390 x 740 x 970 mm | | 1840 x 740 x 970 mm | | 2290 x 740 x 970 mm | |
| Dati per il trasporto - <i>Transport data</i> (20 ft - 40 ft - 40 hc - 13,60 mt) | 24/50/50/53 | | 18/38/38/40 | | 16/32/32/34 | |
| Ripiani - <i>Shelves</i> | 4 rimovibili/removable | | 6 rimovibili/removable | | 8 rimovibili/removable | |
| Classe energetica - <i>Energy efficiency class</i> | | | | | | |

✓ **Griglie rimovibili GN1/1:
4 (N°2 per ogni porta)**
Adjustable shelves GN1/1:
4 (N.2 for each door)

✓ **Rispetto ambientale: Gas R290**
Environmentally friendly: R290

✓ **Alzatina compressa (100 mm)**
On dotation splash back (100 mm)



SOUS-CHEF 2



SOUS-CHEF 3



SOUS-CHEF 4


APPROFONDIMENTO - More details
GASTRONORM 1/1 GN

Mobile in lamiera d'acciaio inox AISI 304
AISI 304 stainless steel sheet cabinet

Vasca in lamiera d'acciaio inox AISI 304
AISI 304 stainless steel sheet tank

Testato a 38°C
Tested at 38°C

Raffreddamento ventilato
Ventilated cooling

